



CONSULT FACTORY FOR SPECIAL CONFIGURATIONS.

		UNITS ARE AVAILABLE IN FAIL CLOCKWISE OR FAIL COUNTERCLOCKWISE, UNIT SHOWN IN FULL CCW (OPEN) POSITION FOR FAIL CLOCKWISE; CCW TO COMPRESS SPRING. GREASED FOR LIFE. PLATED STANDARD SHAFT.	MAX DRIVER BORE & KEY		HANDWHEEL RECOMMENDED ϕ : 36 IN RIM PULL AT MAX TORQUE: 75 LBS TURNS FOR 90°: 150	RATIO: 600:1 TORQUE: 200,000 IN LBS [22597 N-M] TEMPERATURE: -20° TO 150°F [-29° TO 66°C] WEIGHT UNIT: 476 LBS [215.9 KG] DRIVER: 231 LBS [104.8 KG] HANDWHEEL: 17 LBS [7.7 KG]
			MAX IN LINE	MAX		
ϕ 5.000 1.000 X .750 KEY	ϕ 5.250 1.500 X 1.000 KEY					

42-62XXA 3/19/07

HOUSING MOUNTING PATTERN				COVER MOUNTING PATTERN				MANUAL 1/4 TURN ACTUATOR COMMERCIAL GRADE	
MAX	MAX ON CENTER	STD	MIN	MAX	MAX ON CENTER	STD	MIN	DYNATORQUE WWW.DYNATORQUE.COM	DT200 SRD
ϕ 15.500 1-8 UNC	ϕ 15.500 1-8 UNC	ϕ 14.016 1 1/8-7 UNC	ϕ 10.000 5/8-11 UNC	ϕ 15.000 ϕ 1.188	ϕ 15.000 ϕ 1.188	ϕ 14.016 ϕ 1.188	ϕ 12.450 ϕ .688		