



CONSULT FACTORY FOR SPECIAL CONFIGURATIONS

<p>POS 1</p>		<p>POS 2 (STD)</p>		<p>KEYWAY DIAGRAM</p>		<p>GREASED FOR LIFE</p> <p>PLATED INPUT SHAFT</p> <p>MAX STEM HEIGHT: 6.50 [165.1]</p> <p>WORM WHEEL RECESS: .09 [2.2]</p>		<p>HANDWHEEL</p> <p>RECOMMENDED ϕ: 30 IN</p> <p>RIM PULL AT MAX TORQUE: 76 LBS</p> <p>URNS FOR 90°: 300</p>		<p>RATIO: 1200:1</p> <p>TORQUE: 300,000 IN LBS [33895 N-M]</p> <p>TEMPERATURE: -20° TO 150°F [-29° TO 66°C]</p> <p>EST. WEIGHT: 460 LBS [209 KGS]</p>	
<p>HOUSING MOUNTING PATTERN</p>				<p>BORE</p>		<p>MANUAL 1/4 TURN ACTUATOR COMMERCIAL GRADE</p>					
MAX		STD		MIN		MAX		STD		<p>DYNATORQUE DT300</p> <p>WWW.DYNATORQUE.COM</p>	
<p>ϕ 15.500 [393.70] 1-8 UNC</p>		<p>ϕ 14.016 [356.00] 1 1/8-7 UNC</p>		<p>ϕ 10.000 [254.00] 5/8-11 UNC</p>		<p>ϕ 7.000 [177.80] 1.250X.625 KWY</p>		<p>ϕ 6.250 [158.75] 1.500X1.000KWY</p>			

33-63XXA 3/16/07