



ITEM	DESCRIPTION
1	DT36 D-STOP
2	DRIVE COUPLING, D-STOP
3	SOCKET COVER
4	ENGAGEMENT KEY

CONSULT FACTORY FOR SPECIAL CONFIGURATIONS.

ENGAGEMENT KEY NOT SHOWN.

STANDARD 20° TEST POSITION. SHOWN IN HOME POSITION. GREASED FOR LIFE. STANDARD STAINLESS STEEL SHAFT. STANDARD STAINLESS STEEL ENGAGEMENT KEY.				MAX DRIVE COUPLING BORE & KEY				CONSULT FACTORY FOR SPECIAL CONFIGURATIONS AND SWITCH MOUNTING OPTIONS		TORQUE: 63,000 IN LBS [7119 N-M] TEMPERATURE: -20° TO 150°F [-29° TO 66°C] WEIGHT UNIT: 81 LBS [36.8 KG] DRIVER: 28 LBS [12.7 KG] KEY: .9 LBS [.4 KG]	
				MAX IN LINE		MAX					
				Ø1.875 .500 X .375 KEY		Ø2.500 .750 X .500 KEY					
HOUSING MOUNTING PATTERN				COVER MOUNTING PATTERN				PARTIAL STROKE TESTING UNIT COMMERCIAL GRADE			
MAX	MAX ON CENTER	STD	MIN	MAX	MAX ON CENTER	STD	MIN	DYNATORQUE 1934 E. SHERMAN MUSKEGON, MI 49444-1824 (231) 739-1377 FAX (231) 739-4514 WWW.DYNATORQUE.COM		DT36 D-STOP	
Ø9.000 3/4-10	Ø7.875 3/4-10	Ø6.496 3/4-10	Ø6.000 5/8-11	Ø9.000 Ø.812	Ø7.188 Ø.812	Ø6.496 Ø.812	Ø5.500 Ø.562				

50-42XX 8/12/03