



CONSULT FACTORY FOR SPECIAL CONFIGURATIONS

		UNIT SHOWN IN FULL CCW (OPEN) POSITION.  UNITS ARE AVAILABLE IN LOCK CLOSED OR LOCK OPEN, UNIT SHOWN IS LOCK CLOSED.  GREASED FOR LIFE.		<b>MAX DRIVER BORE &amp; KEY</b>		<b>1/2" HEX DRIVE FOR INPUT SHAFT</b>		TORQUE: 3,000 IN LBS [342 N-M] TEMPERATURE: -20° TO 150°F [-29° TO 66°C] WEIGHT UNIT: 11.5 LBS [5.2 KG] DRIVER: 2 LBS [.9 KG]																	
<table border="1"> <tr> <th>MAX</th> <th>MAX ON CENTER</th> <th>STD</th> <th>MIN</th> </tr> <tr> <td>Ø 4.016 3/8-16</td> <td>Ø 3.750 3/8-16</td> <td>Ø 2.756 5/16-18</td> <td>Ø 1.968 1/4-20</td> </tr> </table>		MAX	MAX ON CENTER	STD	MIN	Ø 4.016 3/8-16	Ø 3.750 3/8-16	Ø 2.756 5/16-18	Ø 1.968 1/4-20	<table border="1"> <tr> <th>MAX</th> <th>MAX ON CENTER</th> <th>STD</th> <th>MIN</th> </tr> <tr> <td>Ø 4.250 Ø .406</td> <td>Ø 3.125 Ø .344</td> <td>Ø 2.756 Ø .344</td> <td>Ø 2.756 Ø .344</td> </tr> </table>		MAX	MAX ON CENTER	STD	MIN	Ø 4.250 Ø .406	Ø 3.125 Ø .344	Ø 2.756 Ø .344	Ø 2.756 Ø .344	<b>COMMERCIAL GRADE D-LOCK</b>		<b>DYNATORQUE</b> WWW.DYNATORQUE.COM 4/25/07		<b>DT3 D-LOCK</b>	
MAX	MAX ON CENTER	STD	MIN																						
Ø 4.016 3/8-16	Ø 3.750 3/8-16	Ø 2.756 5/16-18	Ø 1.968 1/4-20																						
MAX	MAX ON CENTER	STD	MIN																						
Ø 4.250 Ø .406	Ø 3.125 Ø .344	Ø 2.756 Ø .344	Ø 2.756 Ø .344																						